

Number Line	Quantity	Text Info
1	4	<p>CONNECTION 18 IN RF,BODY MATERIAL ASTM , 150# VALVE,GATE: VALVE SIZE 18 IN FULL BORE,DESIGN RATING DOUBLE DISC THROUGH CONDUIT,TRIM FLEXIBLE WEDGE: A387 GR.12+STL, A516 GR.60, FULL X-RAY TEST,TYPE STEM: 17- ,OFF, UNI-DIRECTIONAL/LEAK-TIGHT, WELDED RENEWABLE SEAT: ASTM A516 GR.60 TIGHT SHUT A193 B7+CERAMIC COATED, BODY :4PH,SOFTGOODS PACKING MATERIAL: SS304+GRAPHITE, BODY BOLT MATERIAL MATERIAL: SS304+GRAPHITE,STEM DESIGN EXTENDED NUT MATERIAL: A194 2H+CERAMIC COATED, GASKET BONNET,TEMPERATU RATIN DESIGN TEMPERATURE: 320°C / 15°C,FACE TO FACE LE 550 STEM,STYLE BOLTED DESIGN PRESSURE: 8.3/-1 ,MM,OPERATED PROCESS FLUID: CRACKED GAS, FLUID STATE: GAS + COKE PARTICLES BORE,SPECIFICATION FACE FINISH: SMOOTH 125-250 BARG,APPLICATION DECOKE LINE VALVE,PORT TYPE FULL ARE FIRE SAFE DESIGN. API 598 ZERO LEAKAGE, ASME B16.5,FFT MOTORIZED AARH (RA=3.2 TO 6.3 M), VALVES ELECTRICAL ACTUATOR, POWER SUPPLY 3PH 400V 50HZ, WITH HAND WHEEL FOR MANUAL OPERATION GEAR BOX: HAND WHEEL FOR , 300 MOTORIZED CONTROL VALVE 4 STEAM PURGE CONNECTIONS, SIZE 1"- CLASS B16.5, CLASS 300 RF, MANU_PART_NO NO_PART_NR, MANUAL OPERATION, INSPECTION PORT: 8", ANSI MANUFACTURER LOCAL</p>
2	5	<p>RF,BODY MATERIAL ASTM A516 GR.60, VALVE,GATE: VALVE SIZE 24 IN,DESIGN RATING #150,CONNECTION 24 IN CONDUIT GATE VALVE,TRIM FLEXIBLE WEDGE: A387 GR.12+STL, FULL X-RAY TEST,TYPE DOUBLE DISC THROUGH STEM: UNI-DIRECTIONAL/LEAK-TIGHT, WELDED RENEWABLE SEAT: ASTM A516 GR.60, EXTENDED ,TIGHT SHUT OFF A193 B7+CERAMIC COATED, :17-4PH,SOFTGOODS PACKING MATERIAL: SS304+GRAPHITE, BODY BOLT MATERIAL MATERIAL: SS304+GRAPHITE,STEM DESIGN EXTENDED BODY NUT MATERIAL: A194 2H+CERAMIC COATED, GASKET RATIN DESIGN TEMPERATURE: 320°C / 15°C,FACE TO FACE LE STEM,STYLE BOLTED BONNET,TEMPERATU ELECTRICAL MOTORIZED ACTUATOR, POWER SUPPLY 3PH 400V 50HZ, HAND WHEEL FOR 700MM,OPERATED BORE,SPECIFICATION ANSI B16.5, FACE MANUAL OPERATION,APPLICATION CRACKED GAS,PORT TYPE 24 IN FULL M), VALVES ARE FIRE SAFE DESIGN,FFT PROCESS FLUID: CRACKED 6,3 FINISH: SMOOTH 125-250 AARH (RA=3.2 TO PURGE STATE: GAS + COKE PARTICLES, ELECTRICAL MOTORIZED CONTROL GATE VALVE, 4 STEAM GAS, FLUID RF, MANU_PART_NO 300 CONNECTIONS, SIZE 1"- CLASS 300, INSPECTION PORT: 8", ANSI B16.5, CLASS NO_PART_NR, MANUFACTURER LOCAL</p>